Referensi Cepat Selenium WebDriver

Otomasi browser, interaksi elemen, wait, dan assertions

Setup

Instalasi

```
pip install selenium webdriver-manager
# webdriver-manager auto-downloads browser drivers
```

Setup Driver Dasar

```
from selenium import webdriver
from selenium.webdriver.chrome.service import Service
from webdriver_manager.chrome import ChromeDriverManager
driver = webdriver.Chrome(
    service=Service(ChromeDriverManager().install()))
```

Mode Headless

```
options = webdriver.ChromeOptions()
options.add_argument("--headless=new")
options.add_argument("--no-sandbox")
driver = webdriver.Chrome(options=options)
```

Browser yang Didukung

`webdriver.Chrome()`	Google Chrome / Chromium
`webdriver.Firefox()`	Mozilla Firefox (GeckoDriver)
`webdriver.Edge()`	Microsoft Edge (Chromium)
`webdriver.Safari()`	Apple Safari (hanya macOS)

Browser & Navigasi

Navigasi

```
driver.get("https://example.com")
driver.back()                # browser back
driver.forward()             # browser forward
driver.refresh()             # reload page
```

Properti Browser

`driver.title`	Judul halaman saat ini
`driver.current_url`	URL halaman saat ini
`driver.page_source`	Sumber HTML halaman lengkap
`driver.get_cookies()`	Daftar semua cookie

Manajemen Window

```
driver.set_window_size(1920, 1080)
driver.maximize_window()
driver.minimize_window()
driver.quit()                # close all windows, end session
```

Menemukan Elemen

Strategi Locator

```
from selenium.webdriver.common.by import By
driver.find_element(By.ID, "login-btn")
driver.find_element(By.CLASS_NAME, "nav-item")
driver.find_element(By.CSS_SELECTOR, "div.card > h2")
driver.find_element(By.XPATH, "//input[@name='q']")
```

Strategi By

`By.ID`	Cocokkan atribut id elemen
`By.NAME`	Cocokkan atribut name elemen
`By.CLASS_NAME`	Cocokkan class CSS (satu class)
`By.TAG_NAME`	Cocokkan nama tag HTML
`By.CSS_SELECTOR`	CSS selector (paling fleksibel)
`By.XPATH`	Ekspresi XPath
`By.LINK_TEXT`	Teks anchor persis
`By.PARTIAL_LINK_TEXT`	Pencocokan sebagian teks anchor

Temukan Beberapa Elemen

```
items = driver.find_elements(By.CSS_SELECTOR, "li.item")
for item in items:
    print(item.text)
# Returns empty list if none found (no exception)
```

Berinteraksi

Klik & Ketik

```
elem = driver.find_element(By.ID, "search")
elem.clear()                 # clear existing text
elem.send_keys("selenium python")
elem.submit()                # submit parent form
```

Dropdown

```
from selenium.webdriver.support.ui import Select
select = Select(driver.find_element(By.ID, "country"))
select.select_by_visible_text("Canada")
select.select_by_value("ca")
select.select_by_index(2)
```

Properti Elemen

`.text`	Konten teks yang terlihat
`.get_attribute('href')`	Nilai atribut HTML
`.is_displayed()`	True jika elemen terlihat
`.is_enabled()`	True jika elemen interaktif
`.is_selected()`	True jika checkbox/radio dipilih
`.tag_name`	Tag HTML (mis. 'input', 'div')
`.value_of_css_property('color')`	Nilai properti CSS yang dihitung

Wait

Explicit Wait

```
from selenium.webdriver.support.ui import WebDriverWait
from selenium.webdriver.support import expected_conditions as EC
elem = WebDriverWait(driver, 10).until(
    EC.presence_of_element_located((By.ID, "result")))
```

Expected Conditions

`presence_of_element_located`	Elemen ada di DOM
`visibility_of_element_located`	Elemen terlihat di halaman
`element_to_be_clickable`	Elemen terlihat dan aktif
`text_to_be_present_in_element`	Elemen memuat teks yang diharapkan
`alert_is_present`	Alert JavaScript sedang tampil
`staleness_of`	Elemen tidak lagi ada di DOM
`title_contains`	Judul halaman memuat teks

Implicit Wait

```
driver.implicitly_wait(10)  # seconds, applies globally
# Explicit waits are preferred — more precise control
```

Frame & Window

Frame

```
driver.switch_to.frame("frame-name")    # by name/id
driver.switch_to.frame(0)                # by index
driver.switch_to.frame(elem)             # by element
driver.switch_to.default_content()       # back to main
```

Window & Tab

```
original = driver.current_window_handle
driver.switch_to.new_window("tab")       # open new tab
driver.switch_to.window(original)        # switch back
driver.close()                           # close current tab
```

Alert

```
alert = driver.switch_to.alert
print(alert.text)
alert.accept()     # click OK
alert.dismiss()    # click Cancel
alert.send_keys("input text")
```

Screenshot

Ambil Screenshot

```
driver.save_screenshot("page.png")       # full page
elem = driver.find_element(By.ID, "chart")
elem.screenshot("chart.png")             # single element
```

Screenshot sebagai Base64

```
b64 = driver.get_screenshot_as_base64()
png = driver.get_screenshot_as_png()     # bytes
```

Actions

Action Chains

```
from selenium.webdriver.common.action_chains import ActionChains
actions = ActionChains(driver)
actions.move_to_element(menu).click().perform()
```

Aksi Keyboard

```
from selenium.webdriver.common.keys import Keys
elem.send_keys(Keys.ENTER)
elem.send_keys(Keys.CONTROL, "a")       # select all
actions.key_down(Keys.SHIFT).click(elem).perform()
```

Aksi Mouse

`.click(elem)`	Klik elemen
`.double_click(elem)`	Klik ganda elemen
`.context_click(elem)`	Klik kanan elemen
`.move_to_element(elem)`	Arahkan kursor ke elemen
`.drag_and_drop(src, dst)`	Seret dari sumber ke tujuan
`.click_and_hold(elem)`	Tekan dan tahan tombol mouse
`.release()`	Lepas tombol mouse

Assertions

Assertions Umum (pytest)

```
assert "Dashboard" in driver.title
assert driver.find_element(By.ID, "msg").text == "Done"
assert driver.current_url.endswith("/home")
assert len(driver.find_elements(By.CSS_SELECTOR, "tr")) > 0
```

Assertions Berbasis Wait

```
WebDriverWait(driver, 5).until(             # appears
    EC.visibility_of_element_located((By.ID, "success")))
WebDriverWait(driver, 5).until(             # disappears
    EC.invisibility_of_element_located((By.ID, "spinner")))
```

Eksekusi JavaScript

```
result = driver.execute_script("return document.title")
driver.execute_script(
    "arguments[0].scrollIntoView(true);", elem)
```

Referensi Cepat Selenium WebDriver

Pola Umum

Pola Page Object

```
class LoginPage:
    URL = "/login"
    user_loc = (By.ID, "username")
    def login(self, drv, user, pwd):
        drv.find_element(*self.user_loc).send_keys(user)
```

Context Manager

```
from selenium import webdriver
with webdriver.Chrome() as driver:
    driver.get("https://example.com")
    print(driver.title)
# driver.quit() called automatically
```

Retry & Cleanup

```
try:
    driver.get("https://example.com")
    WebDriverWait(driver, 10).until(
        EC.element_to_be_clickable((By.ID, "btn")))
finally: driver.quit()
```